

Product Discontinuation of the UMG 605-PRO

Dear Sir or Madam,

We would like to inform you about an upcoming change in our product portfolio that affects the UMG 605-PRO.

As part of our ongoing portfolio development, the **UMG 605-PRO** is being discontinued. With this step, we are consistently aligning our portfolio with long-term availability, technological advancement, and future-proof system solutions.

Product Discontinuation Timeline - Please note the following key dates:

Last order: 31 August 2027

Last delivery: 30 November 2027

End of standard support: 30 November 2028

After the standard support period expires, Janitza will no longer provide regular technical support, firmware updates, or repairs for the affected device. Warranty obligations for devices delivered prior to this date will, of course, be fulfilled in accordance with the terms of the contract. New software features and non-security-critical bug fixes will no longer be released after this date.

Migration Recommendation

For many common applications, the **UMG 801**, offers you a powerful and proven alternative from our current product portfolio.

The benefits of the UMG 801 at a glance

- Capture, analysis and document-tation of disturbance variables
- Easy integration into a higher- level system
- Modular expandable

Our sales staff and solution partners are available to answer technical questions or advise you on alternative devices.

Kind regards,


ppa. Thomas Hilbig
Vice President Product Management

Affected products / Conversion table

<i>Item number</i>	<i>Discontinued product</i>	<i>Item number</i>	<i>Alternative</i>
52.16.229	UMG 605-PRO 20-55 V AC	52.31.003	UMG 801
52.16.028	UMG 605-PRO 50-110 V AC	52.31.230	Modul 800-CT8-A
52.16.227	UMG 605-PRO 95-240 V AC	52.31.234	Modul 800-CT8-LP
52.16.083	UMG 605-PRO, Option BACnet	52.31.214	Modul 800-DI14
		52.31.247	Modul 800-CT24
		52.31.301	Modul 800-CT12-SVD-US
		52.31.210	Modul 800-CON
		52.31.242	Modul 800-CON-RJ45

UMG 801**BASIC DATA**

- 8 current measurement channels with 1/5 A inputs
- 4 Multifunction channels

POWER QUALITY

- High sampling frequency of 51.2 kHz
- 1024 Samples for the voltage measurement
- 1000 V CAT III
- Voltage up to 127th harmonics
- THD-U and THD-I
- Event and transient detection

COMMUNICATION

- OPC UA
- Modbus TCP/IP
- Modbus RTU

MODULAR EXPANSION**Add more functions through modules**

- 800-CT8-A
- 800-CT8-LP
- 800-DI14
- 800-CT24
- 800-CT12-SVD-US
- 800-CON
- 800-CON-RJ45

