

Product Discontinuation of the ProData II

Dear Sir or Madam,

We would like to inform you about an upcoming change in our product portfolio that affects the ProData II.

As part of our continuous portfolio optimization and to ensure long-term product availability, reliability, and technological relevance, the ProData II will be discontinued. This decision is based on ongoing technical development.

Product Discontinuation Timeline

Please note the following key dates:

Last order: 30 November 2026

Last delivery: 31 May 2027

End of standard support: 31 May 2028

After the end of the standard support, Janitza will no longer provide regular technical support, firmware updates and repairs for the ProData II. Warranty obligations for devices delivered prior to this date will, of course, be fulfilled in accordance with contractual terms. However, no new software features or non-critical bug fixes will be released.

Migration Recommendation

To ensure continuity and future-proof system planning, we recommend the **UMG 800 and the Module 800-DI14** as the successor to the ProData II.

Your benefits with the UMG 800 and the Module 800-DI14

- Compact and space-saving
- Modular expandable
- Optimal communications and data management

Our sales staff and solution partners are available to answer technical questions or advise you on alternative devices.

Kind regards,



Michael Kadziela
Managing Director

Affected products / Conversion table

<i>Item number</i>	<i>Discontinued product</i>	<i>Item number</i>	<i>Alternative</i>
52.24.011	ProData II	52.38.001	UMG 800, UL
		52.38.002	UMG 800
		52.31.214	Module 800-DI14

UMG 800**BASIC DATA**

- Size – 2 sub-units
- 300 V CAT III
- Measuring accuracy: Voltage 0.2 %
- 4 GB data memory
- High sampling frequency (51.24 kHz)
- 1024 samples for voltage measurement
- Effective values of half waves 10 ms

MODULARITY

- Expandable by up to 12 + 1 modules
- Up to 96 current measurement inputs
- Up to 182 digital inputs
- Up to 100 m measurement point bridging via the connector module

COMMUNICATION

- OPC UA
- NTP
- Modbus TCP/IP Gateway for up to 31 slaves

Modul 800-DI14**DIGITAL INPUTS**

- Provides 14 additional digital inputs
- Status recording of, for example, door contacts or status contacts (fans, valves and other equipment)
- Triggering of actions

COMPACT

- Compact 1 sub-unit size

MODULE SLOTS

- Requires 1 module slot

