

Product Discontinuation of the UMG 806 and Modules

Dear Sir or Madam,

We would like to inform you about an upcoming change in our product portfolio that affects the UMG 806 and the relevant modules.

As part of our ongoing portfolio development, the **UMG 806** is being discontinued. With this step, we are consistently aligning our portfolio with long-term availability, technological advancement, and future-proof system solutions.

Product Discontinuation Timeline - Please note the following key dates:

Last order: 31 August 2027

Last delivery: 30 November 2027

End of standard support: 30 November 2028

After the standard support period expires, Janitza will no longer provide regular technical support, firmware updates, or repairs for the affected device. Warranty obligations for devices delivered prior to this date will, of course, be fulfilled in accordance with the terms of the contract. New software features and non-security-critical bug fixes will no longer be released after this date.

Migration Recommendation

As the successor to the UMG 806, we are currently developing the UMG 105, which will enable a seamless transition for your project planning.

For many common applications, the **UMG 103-CBM** offers you a powerful and proven alternative from our current product portfolio.

Your benefits with the UMG 103-CBM

- Compact DIN rail measuring device
- Large measurement data storage
- Cost-effective and universally applicable

Our sales staff and solution partners are available to answer technical questions or advise you on alternative devices.

Kind regards,


ppa. Thomas Hilbig
Vice President Product Management

Affected products / Conversion table

<i>Item number</i>	<i>Discontinued product</i>	<i>Item number</i>	<i>Alternative</i>
14.02.041	UMG 806	52.28.001	UMG 103-CBM
14.02.042	UMG 806 LP		
14.02.019	MODUL 806-ED1		
14.02.020	MODUL 806-EI1		
14.02.051	MODUL 806-EC1 (UL)		

BASIC DATA

- Auxiliary voltage up to 277 V
- Measured voltage up to 480 V
- Effective energy class 0.5S (DIN EN62053-22:2003) for .../5 A current transformer

COMMUNICATION AND INTERFACE

- RS485 with ground connection and 3-pole plug (A, B, GND)
- Galvanic separation incl. DC/DC converter

MEASURED DATA RECORDING

- 400,000 measured values can be saved – this represents a period of 144 days (If all profiles are activated)
- Measured data with precise timestamp

ADDITIONAL FUNCTIONS

- CREST factor - Measurement for the power quality
- 2 comparator groups with 3 comparators each (A-C)

